



PULSEAUDIO™

2 Channel, Class D AMPLIFIERS

PA2X25



PA2X60



PA2X125



PA2X150



- Class D Digital Amplifier
- RCA and 1/8" Stereo Inputs
- Mixes audio when both inputs are connected and live
- Stereo and Mono/Bridge Modes
- Automatically goes into standby after 5 minutes of inactivity
- Source Sensing to come out of standby when a connected source begins to play
- AC 115/230V IN



LEARN MORE AT VANCO1.COM



2 Channel, Class D AMPLIFIERS

Model Number:	PA2X25	PA2X60	PA2X125	PA2X150
Power Output (RMS @ 8 Ω)	25Wx2	60Wx2	125Wx2	150Wx2
Power Output (RMS @ 4 Ω)	45Wx2	90Wx2	180Wx2	225Wx2
Bridge Output (RMS @ 8 Ω)	90W	180W	360W	450W
Total Harmonic Distortion (THD):	<1%(Rated power: 25W @ 8Ω)	<1%(Rated power: 60W @ 8Ω)	<1%(Rated power: 125W @ 8Ω)	<1%(Rated power: 150W @ 8Ω)
Signal to Noise:	>90 dB A WTD	>90 dB A WTD	>90 dB A WTD	>90 dB A WTD
Frequency Response:	20Hz-20KHz +0/- 2dB@ 8Ω	20Hz-20KHz +0/- 2dB@ 8Ω	20Hz-20KHz +0/- 2dB@ 8Ω	20Hz-20KHz +0/- 2dB@ 8Ω
Line Level Input Sensitivity:	700mV	700mV	700mV	700mV
Thermal Protection:	Yes	Yes	Yes	Yes
Short Protection:	Yes	Yes	Yes	Yes
Dimension:	143mm x 95mm x 45mm (WxDxH)	214mm x 250mm x 44mm (WxDxH)	214mm x 250mm x 44mm (WxDxH)	214mm x 250mm x 44mm (WxDxH)
Weight:	0.6kG	1.32kG	1.65kG	1.65kG