## Class D 120 & 220 Watt Subwoofer Amplifiers





The A120 and A220 amplifiers have all the muscle you need to drive even the most demanding subwoofers to house-thumping levels. Both the 120 and 220 watt options have stereo/mono inputs that can receive full band line level audio from an amplifier, receiver, preamp, or LFE output on just about any appropriately featured device. The adjustable crossover allows fine-tuning the low frequency input setting to properly complement any full-range speakers or room conditions.

<b>Product Specifications</b>	A120 Subwoofer Amplifier	A220 Subwoofer Amplifier
Max power output (per channel)	80W @ 8ohm / 120W @ 4ohm	120W @ 8ohm / 220W @ 4ohm
Total harmonic distortion	1%	< 1%
Frequency response	40Hz-160Hz +/- 1dB	20Hz-160Hz +/- 1dB
Signal to noise	95dB	95dB
Input sensitivity	200mV	2mV @ 50Hz
Crossover	40Hz-160Hz	40-160Hz
Phase	0-180°	0-180°
Trigger input	+12VDC to +24VDC	+12VDC to +24VDC
Line voltage range	100-240 VAC	110-120 / 220-224 VAC
Standby power	1.8W	1.8W
Max power consumption	180W	280W
Dimensions	5.7" W x 1.8" H x 5.0" D	8.4" W x 1.7" H x 9.8" D
	143mm W x 45mm H x 125mm D	214mm W x 44mm H x 250mm D
Weight	1.75lbs (0.79kg)	2.9lbs (1.32kg)