

Minimum switch requirements:

Here is a list of switch feature requirements for our EVO-IP AV Over IP Solution. All features listed must be present when finding a switch to use with our EVO-IP Lite, EVO-IP 1.0, and EVO-IP 2.0 platforms.

[Please refer to our website for the latest version of this document.](#)

- Managed
- Multi-cast & multi-layer (2+ or better)
- Jumbo frames (9000 bytes or better)
- IGMP snooping
- 1G switch for single switch applications
- 10G switch for multi-switch applications

We are always working with and testing other brands of switches to be able to provide additional setup guides and support when using EVO-IP. The list of models and brands below represent switches we have in house and have tested and provided setup guides for proper configuration. If you have any switch questions or recommendations, do not hesitate to reach out and we will follow up and fill you in with any changes or test results. Switches that can be used with EVO-IP products include but are not limited to the following:

Cisco

SG250
SG300
SG350X
SG500
SG500X

TP Link

TL-SG3428MP
TL-SG3428XMP
TL-SG3452P
TL-SG3452XP

Niveo

NRS24TP

Luxul

AMS/XMS-1208P
AMS/XMS-2624P
AMS-4424P
XMS-5248P
XMS-7048P
SW-610-24P
SW-610-48P
SW-515/615 Series

Trendnet

TL2-G244
TL2-PG284
TPE-3102WS
TPE-3542S
TPE-3524SF

Netgear

GS728TPV2
GS728TPPV2
M4250 Series
M4350 Series

Ubiquiti

ES-16-150W
ES-24-250W
ES-24-500W
ES-48-500W
ES-48-750W