



Vanco EVMX44SL 4X4 HDMI Matrix ELAN Driver
V1.0 rev20160407

Overview

This driver integrates a Vanco EVMX44SL 4X4 HDMI Matrix into your ELAN control system. The driver was created and tested on a gSC2 series controller using g!Viewer. To use this driver, add the driver to the system, and follow the setup.

Specification

This package includes the following:

- Compiled ELAN Driver (EVMX44SL.EDRVC)
 - Controls hardware device.

SERIAL (RS-232) Connection

The driver communicates to and from the device through an SERIAL (RS-232) connection and must be connected in order for the driver to function.

Setup

1. Add the driver to the controller as a "Zone Controller" in g!Tools Configurator under the "Media" menu.
2. Add a new communication device, selecting "Serial Port" and the "COM Port" that the matrix is connected to.
3. Select the new communication device in the driver, and hit "Apply".
4. Configure the inputs under "Sources" and the outputs under "Zones".
5. Device specific commands (Switch Mode, Switch Time, Input Mode, Scaler/Auto, Multiviewer Mode, Multiviewer Audio, Multiviewer Main, Video Wall Adjust X/Y, and Video Wall Input Channel) are available for event mapping. Device specific options (Display Mode, Beep, and Border) are available as options on output settings pages.



www.vanco1.com

