



Updating the firmware for the EVO-IP system

Below are the steps that are required to perform a firmware update locally on the EVOIPCTL1 control box. Please check the product webpage at www.vanco1.com for the most up to date firmware.

1. Connect to the EVO-IP web based GUI by entering the IP address of the EVOIPCTL1 control box, or by typing http://evo-ip.local into any web browser on the local network.

2. Enter in the account username and password (both are admin by default).

| HDMI over IP × | | Θ - ۵ × |
|---|---|--------------------------------|
| ← → C O Not secure 192.168.0.183/login#!/ | mapping | ☆ : |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | Account | |
| | Account | |
| | Password | |
| | | |
| | Login | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | → 010.111 |
| Type here to search | | x ^R ^ 😻 7/30/2018 🐻 |
| | 4 | |
| | 1 | |
| _ | | |
| Fo | or Technical Support Call Toll Free: 800-626-6445 | |
| | 506 Kingsland Dr, Batavia, IL 60510 | |
| | | ADVANCINSC |



3. click on the **Smart Controller** mode and a new window or tab will open on the browser.

| | MATI | RIX | SmartController ○ 2016-07-30 08-49-12 Presets Save as ^ Load ✓ III |
|---------------------|-------------|-----|--|
| X4 Narrs | Display(RX) | All | Total: 0 📾 |
| Video Wall | Source(TX) | | Totat: 0 📼 |
| O Schedule | | | |
| | | | |
| Access | | | |
| Setup III Log | | | |
| Smart Controller | | | |
| cog ton | | | |

4. Once the new window or tab opens, enter the username and password (both are **admin** by default), then click "Login".





5. After logging in, click on the **Maintenance** menu. Click on **Start Upgrade/Status Firmware** and the controller will search for and install the most recent firmware if it has not been done already.

VOLUTION

| / C HDMI over IP X | Smart Controller x | | θ - σ × |
|-----------------------|----------------------|-------------------|------------------------------|
| ← → C © 192.168.0.183 | 3.8080/#/maintain | | en Q, ☆ |
| | | | 🖯 Help 🛔 admin + |
| 🗆 tysen 🔹 🕴 | | | |
| Coul | Maintenance | | |
| ➤ Martenarce 1. | | | |
| | System Configuration | | |
| | | Reset to default. | 10 Reset to default |
| | | | |
| | Fernicare Upgrade | | |
| | | | 2 |
| | | Upgrade firmware | Start UpgradeStatus Firmware |
| | | | |
| | Restart Device | | |
| | | Restart Device | D Restart Device |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

6. Once the Firmware status/install is complete, the EVOIPCTL1 will automatically reboot.

| HDMI over IP × | Smart Controller × | Θ – 🗇 🗙 |
|--|--|-------------------|
| \leftrightarrow \rightarrow C \bigcirc 192.168.0.183 | 3:8080/#/maintain | ~ Q ☆ : |
| | | 😯 Help 🛔 admin 🗸 |
| System Cloud | Maintenance Autorestantative 4 seconds | |
| A Maintenance | System Configuration | |
| | Reset to default O Reset to default | |
| | Firmware Upgrade | |
| | Upgrade Firmware V Done! | |
| | Upgrade Progress checking the lastest firmare with St B00000000F687867 descloading the firmare firmare firmare firmare formation complete velidating file format extracting file post install files postinatall done t | |
| | Restart Devke | _ |
| | Restart Device O Restart Device | |
| | | 051 AM |
| U Type here to search | ch 🔱 🐠 📴 🛄 🔚 📴 🧑 🥝 | ^ 🚺 🗗 7/30/2018 📆 |

For Technical Support Call Toll Free: 800-626-6445 506 Kingsland Dr, Batavia, IL 60510

